

400 Christian Lane ■ PO Box 504 ■ Kensington, CT 06037 ■ Tel: (860) 828-6501 ■ Fax: (860) 828-4701 www.delmarproducts.com

OPAQUE RIGID PVC

Finish - CALENDAR MATTE

Properties	Test Method	Value
Thickness	Micrometer	+/- 5%
Dimensions	Steel Rule	+/- 1/32"
Squareness	Steel Rule	+/- 1/32"
Grain	Orientation	long / length (gauge x width x length)
Color	Spectrophotometer	$\Delta E \le 1$
Gloss @ 85°	Ref. ASTM D-2457	5% +/- 3% Print (A) Side
Surface Roughness (RA)	Electronic Surface Tester	67 microinches +/- 10 Print (A) Side
Surface Tension	Wetting Solution	Dyne 38 minimum Print (A) Side
Vicat	ASTM D-1525	78° C +/- 2 °
Specific Gravity	ASTM D792	1.35 +/04
Dimensional Stability 140° C 10 minutes	ASTM 1204	MD < -9%, CD < +2%

NOTE: This information is based upon the results of our testing and raw material supplier documentation. Delmar Products Inc. makes no warranty of merchantability, whether expressed or implied. Product usage and ability to perform is the consumer's responsibility. Product can be originated specifically for consumer's application with our warranty of consistent repetition.